

Ü` àà^!ÁÚ[~!&^Q&É
 6Í ÁÓ[, æ•çã, ÁÚá
 Ôæ ã!ã*^ÁÚÞÁFÜÁÞH
 Í FJ-Í GÈÏ || €
 Í FJ-Í G È GGF (Fax)

Product Data Sheet

8!Gc`j Y

Solvent/Stripper

Product Description- *Fi VVyf`Gci fW`8!Gc`j Y* is a water soluble, organic solvent containing no aromatics or petroleum distillates. **8!Gc`j Y** is designed to provide maximum stripping effectiveness while incorporating a high flash point and low toxicity. **8!Gc`j Y** replaces most industrial solvents such as chlorinated hydrocarbons (methylene chloride, carbon tetrachloride and 1,1,1 trichlorethane) when used on cured polymers.

Uses- **8!Gc`j Y** solvent/stripper is designed to strip polyurea, polyurethane, epoxies and polyester resins.

Effective with-

- Grease
- Oil
- Inks
- Waxes
- Rubber residues
- Lacquers
- Latex paint
- Oil based paint

Advantages:

- VOC level acceptable to SCAQMD region
- Non toxic
- Easy to apply
- Non-flammable
- Flash point >200°F
- Low odor
- Indefinite shelf life
- Will not cause hazardous polymerization
- Low evaporation rate
- Not R.C.R.A or DOT regulated. **8!Gc`j Y** water solubility allow for safe use.

Physical Properties-	
Appearance	Clear liquid
Odor	Mild sweet odor
Specific gravity @ 77°F	1.08
Flash point	>200°F
The value ranges stated in this Technical Data Sheet are based on system processing under laboratory condition.	

Limitations- Reacts violently with strong acids or bases.

Packaging-

- Fifty Five Gallon: 55 gallon drum. Drum containers filled by weight, volume is closely approximated.
- Five Gallon: 5 gallon container
- One Gallon: 1 gallon container

Preparation & Application- Apply **8!Gc`j Y** liberally or employ baths where possible for stationery stripping. **8!Gc`j Y** applied by brush. May be used to strip various gun parts – Consult *Fi VVyf`Gci fW`8!Gc`j Y*. Not recommended for flushing plural component machines.

Safety- Review MSDS at VersaFlex.com

Basic safety for personal protection is:

- Long sleeve overalls or disposable Tyvex overalls
- Rubber gloves
- Splash shield or safety glasses with splash guards
- Rubber or leather boots
- Respirator
- Do not use near high heat or open flame
- Do not take internally
- Keep out of reach of children

Shelf Life- One year from date of shipment, in original, unopened factory containers, under normal storage conditions of 55°F to 95°F (18°-35°C).

Technical Services- Sales and Customer Support | FJH G&H | | €

Warranty- *VVYf Gci fW Incorporated* will refund the price of or replace, at its election, product it finds to be defective provided the product has been used properly. Except as expressly stated above, the company makes no warranty of merchantability and no warranty of fitness for any particular purpose, nor does it make any warranty, expressed or implied, of any nature whatsoever with respect to the product of its use. In no event shall the company be liable for delay caused by defects, for loss of use, for indirect, special or consequential damages, or for any changes or expenses of any nature incurred without its written consent.