



RS-400

Red Rubber Sheeting

High abrasion resistant, engineered for the mining industry



Applications

- Cyclones
- Separators
- Classifiers
- Vessels
- Chutes
- Pipe Linings
- Skirting

Benefits

- Resistant to abrasion
- High resilience
- Reduces corrosion
- Vibration & noise absorbing

Available Thickness

Metric	Imperial
1-50mm	1/32" - 2"

Roll Sizes

Metric	Imperial
1.2m x 10m	4' x 33'
1.4m x 10m	4.6' x 33'
1.5m x 10m	4.92' x 33'
Custom sizes available	

Specifications

Color	Red	Red
Density (gr/cc)	.98 lb/ft ³	.98 g/cm ³
Durometer (Shore A)	38+-5 Sh A	38+-5 Sh A
Tensile (min) kg / cm ³	3415 PSI	240 kg/cm ²
Elongation (%)	810%	810%
Tear (kg / cm -- min.)	224 lbs/inch	40 kg/cm
Abrasion Resistance	80 mm ³	80 mm ³
Compression 70°C 24 hrs	15%	15%
Temperature Range	-40°F to 158°F	-40°C to 70°C

For more information or to place an order, contact us today.

Tel: 519-620-4440 Fax: 519-624-7221