

## RS-400

# Red Rubber Sheeting

High abrasion resistant, engineered for the mining industry



### Applications

- Cyclones
- Separators
- Classifiers
- Vessels
- Chutes
- Pipe Linings
- Skirting

### Benefits

- Resistant to abrasion
- High resilience
- Reduces corrosion
- Vibration & noise absorbing

### Available Thickness

Metric	Imperial
1-50mm	1/32" - 2"

### Roll Sizes

Metric	Imperial
1.2m x 10m	4' x 33'
1.4m x 10m	4.6' x 33'
1.5m x 10m	4.92' x 33'
Custom sizes available	

### Specifications

	Red	Red
Color	Red	Red
Density (gr/cc)	.98 lb/ft <sup>3</sup>	.98 g/cm <sup>3</sup>
Durometer (Shore A)	38+-5 Sh A	38+-5 Sh A
Tensile (min) kg / cm <sup>3</sup>	3415 PSI	240 kg/cm <sup>2</sup>
Elongation (%)	650%	650%
Tear (kg / cm -- min.)	224 lbs/inch	40 kg/cm
Abrasion Resistance	80 mm <sup>3</sup>	80 mm <sup>3</sup>
Compression 70°C 24 hrs	15%	15%
Temperature Range	-40°F to 158°F	-40°C to 70°C

*For more information or to place an order, contact us today.*